

Silicone Products for Personal Care

(For North and South America)



- Dimethyl Silicone Fluids
- Volatile Silicone Fluids
- Methyl Phenyl Silicone Fluids
- Amino Modified Silicones
- Other Modified Silicone
- Fluid Compounds
- Dimethyl Silicone Blends
- High Polymerization Dimethiconols
- Amino Gums
- Silicone Emulsions
- Polyether Modified Silicones
- Polyglycerin Modified Silicones
- Silicone Gels
- Silicone Acrylates
- Trimethylsiloxysilicates
- Silicone Film Formers
- Silicone Powders
- Powder Treatments
- Powder Dispersions

Contents

Product List

1 Dimethyl Silicone Fluids	P3	11 Polyether Modified Silicones	P7
2 Volatile Silicone Fluids	P4	12 Polyglycerin Modified Silicones	P7
3 Methyl Phenyl Silicone Fluids	P4	13 Silicone Gels	P8-9
4 Amino Modified Silicones	P4	14 Silicone Acrylates	P10
5 Other Modified Silicone	P4	15 Trimethylsiloxysilicates	P11
6 Fluid Compounds	P4	16 Silicone Film Formers	P11
7 Dimethyl Silicone Blends	P5	17 Silicone Powders	P12
8 High Polymerization Dimethiconols	P5	18 Powder Treatments	P12
9 Amino Gums	P5	19 Powder Dispersions	P13
10 Silicone Emulsions	P6		

Data

Dimethyl silicone fluid soluble in various solvents	P14
Volatile Data	P14
Bake-on Temperature and Processing Time	
Methyl Hydrogen Polysiloxane	P14
Solubility Dimethicone	P15
Compatibility (20%)	
Polyether Modified Silicone Fluid, Polyglycerin Modified Silicone Fluid	P15

Handling Precautions	P15
-----------------------------------	-----

1 Dimethyl Silicone Fluids

Grade	Parameter	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Volatile Matter 150°C x 24 h, %	Pour Point °C	Flash Point °C
DM-FLUID-A-1cs		TRISILOXANE	1	0.818	1.382	Boiling point 153°C	-100	37
DM-FLUID-1.5cs		DIMETHICONE	1.5	0.852	1.387	Boiling point 194°C	< -90	64
DM-FLUID-2cs		DIMETHICONE	2	0.873	1.391	Boiling point 229°C	< -120	88
DM-FLUID-A-5cs		DIMETHICONE	5	0.915	1.396	< 40* ¹	< -110	102
DM-FLUID-A-6cs		DIMETHICONE	6	0.925	1.397	< 5.0* ¹	< -100	174
DM-FLUID-A-10cs		DIMETHICONE	10	0.935	1.399	< 40	< -100	> 160
DM-FLUID-A-20cs		DIMETHICONE	20	0.950	1.400	< 4.0	< -60	> 260
DM-FLUID-A-30cs		DIMETHICONE	30	0.955	1.401	< 1.5	< -55	> 280
DM-FLUID-A-50cs		DIMETHICONE	50	0.960	1.402	< 0.5	< -50	> 310
DM-FLUID-A-100cs		DIMETHICONE	100	0.965	1.403	< 0.5	< -50	> 315
DM-FLUID-A-200cs		DIMETHICONE	200	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-A-300cs		DIMETHICONE	300	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-A-350cs		DIMETHICONE	350	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-A-500cs		DIMETHICONE	500	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-1,000cs		DIMETHICONE	1,000	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-3,000cs		DIMETHICONE	3,000	0.970	1.403	< 0.5	< -50	> 315
DM-FLUID-A-5,000cs		DIMETHICONE	5,000	0.975	1.403	< 0.5	< -50	> 315
DM-FLUID-6,000cs		DIMETHICONE	6,000	0.975	1.403	< 0.5	< -50	> 315
DM-FLUID-10,000cs		DIMETHICONE	10,000	0.975	1.403	< 0.5	< -50	> 315
DM-FLUID-12,500cs		DIMETHICONE	12,500	0.975	1.403	< 0.5	< -50	> 315
DM-FLUID-30,000cs		DIMETHICONE	30,000	0.976	1.403	< 0.5	< -50	> 315
DM-FLUID-50,000cs		DIMETHICONE	50,000	0.976	1.403	< 0.5	< -50	> 315
DM-FLUID-60,000cs		DIMETHICONE	60,000	0.976	1.403	< 0.5	< -50	> 315
DM-FLUID-100,000cs		DIMETHICONE	100,000	0.977	1.403	< 0.5	< -50	> 315
DM-FLUID-300,000cs		DIMETHICONE	300,000	0.977	1.403	< 0.5	< -50	> 315
DM-FLUID-500,000cs		DIMETHICONE	500,000	0.978	1.403	< 0.5	< -50	> 315
DM-FLUID-1,000,000cs		DIMETHICONE	1,000,000	0.978	1.403	< 0.5	< -50	> 315

* The commercial name in US is DM-FLUID-xxx, outside of US is KF-96-xxx.

*1: 105°C x 3 h

(Not specific values)

2 Volatile Silicone Fluids

Parameter Grade	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Freezing Point °C	Boiling Point °C	Flash Point °C	Surface Tension 25°C, mN/m
KF-995	CYCLOPENTASILOXANE	4.0	0.956	1.396	-40	210	77	17.8
TMF-1.5	METHYL TRIMETHICONE	1.5	0.847	1.386	-83	191	60	16.8

* Non-linear type

(Not specific values)

3 Methyl Phenyl Silicone Fluids

Parameter Grade	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Volatile Matter 150°C x 24 h, %	Pour Point °C	Flash Point °C
F-5W-0-100cs	DIPHENYL DIMETHICONE	100	0.995	1.427	< 0.5	< -65	> 315
F-5W-0-1,000cs	DIPHENYL DIMETHICONE	1,000	1.000	1.427	< 0.5	< -65	> 315
KF-53	DIPHENYL DIMETHICONE	175	1.055	1.485	< 0.3	< -30	> 300
KF-54	DIPHENYL DIMETHICONE	400	1.070	1.505	< 0.5	< -30	> 300
KF-56A	DIPHENYLSILOXY PHENYL TRIMETHICONE	15	0.995	1.498	15*	< -55	> 100
KF-54HV	DIPHENYL DIMETHICONE	5,000	1.080	1.503	< 0.5	< -30	> 315

* 105°C x 3h

(Not specific values)

4 Amino Modified Silicones

Parameter Grade	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C
KF-8004	AMODIMETHICONE	800	0.980	1.408
KF-8005S	AMINOETHYLAMINOPROPYL DIMETHICONE	1,600	0.973	1.404
KF-8015	AMINOPROPYL DIMETHICONE	50,000-100,000	0.975	1.405
KF-867S	AMODIMETHICONE	1,300	0.980	1.407

(Not specific values)

5 Other Modified Silicone

Parameter Grade	INCI	Modified Type	Melting Point °C	Specific Gravity 25°C
KF-7002	STEAROXYMETHICONE/DIMETHICONE COPOLYMER	Stearoxy	40-50	0.890

(Not specific values)

6 Fluid Compounds

Parameter Grade	INCI	Appearance	Viscosity 25°C, mPa·s	Specific Gravity 25°C
S-6W-6	SIMETHICONE	Light gray translucent liquid	300	1.01
S-6W-9	SIMETHICONE	Light gray translucent paste	2,500	1.01

(Not specific values)

7 Dimethyl Silicone Blends

Grade	Parameter	INCI	Component A	Viscosity 25°C, mPa·s	Specific Gravity 25°C	Refractive Index 25°C	Dimethicone Gum Content, %	Solvent
			Component B					
KF-9008		DIMETHICONE		30,000	0.961	1.397	20	KF-995
		CYCLOPENTASILOXANE						
KF-9011		DIMETHICONE		1,600	0.959	1.397	10	KF-995
		CYCLOPENTASILOXANE						
KF-9013		DIMETHICONE		15,000	0.954	1.401	15	DM-FLUID-A-20cs
		DIMETHICONE						
KF-9014		DIMETHICONE		6,000	0.960	1.397	15	KF-995
		CYCLOPENTASILOXANE						
MK-15H		DIMETHICONE		45,000	0.958	1.402	20	DM-FLUID-A-20cs
		DIMETHICONE						
X-21-5495		DIMETHICONE		3,000	0.961	1.397	15	KF-995
		CYCLOPENTASILOXANE						
KF-9028		DIMETHICONE		3,000	0.965	1.398	20	KF-995
		CYCLOPENTASILOXANE						
KF-9030		DIMETHICONE		5,000	0.955	1.401	20	DM-FLUID-A-20cs
		DIMETHICONE						

(Not specific values)

8 High Polymerization Dimethiconols

Grade	Parameter	INCI	Component A	Viscosity 25°C, mPa·s	Specific Gravity 25°C	Refractive Index 25°C	Dimethiconol Content, %	Solvent
			Component B					
X-21-5613		DIMETHICONOL		5,000	0.957	1.401	20	DM-FLUID-A-20cs
		DIMETHICONE						
X-21-5666		DIMETHICONOL		15,000	0.960	1.398	30	KF-995
		CYCLOPENTASILOXANE						
X-21-5847		DIMETHICONOL		22,000	0.975	1.404	100	—
X-21-5849		DIMETHICONOL		100,000	0.977	1.403	100	—

(Not specific values)

9 Amino Gums

Grade	Parameter	INCI	Component A	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Amino Gum Content %	Solvent
			Component B					
KF-8017		AMINOPROPYL DIMETHICONE		2,000	0.956	1.401	10	DM-FLUID-A-20cs
		DIMETHICONE						
KF-8018		AMINOPROPYL DIMETHICONE		2,000	0.961	1.397	10	KF-995
		CYCLOPENTASILOXANE						
KF-8020		AMINOPROPYL DIMETHICONE		40,000	0.956	1.401	20	DM-FLUID-A-20cs
		DIMETHICONE						

(Not specific values)

10 Silicone Emulsions

Parameter Grade	INCI	Composition %	Appearance	Viscosity 25°C, mPa·s	Base Oil	Silicone Solvent	Silicone Content %	PH 25°C	Ionic Property
KM-901	Component A : DIMETHICONE	50.0	Milky white emulsion	100	DM-FLUID-60,000cs	—	50	3.0	Nonionic
	Others	6.25							
KM-902	Component A : DIMETHICONE	50.0	Milky white emulsion	100	DM-FLUID-500,000cs	—	50	3.0	Nonionic
	Others	6.15							
KM-903	Component A : DIMETHICONE	18.0	Milky white emulsion	1,000	Dimethicone gum	DM-FLUID-A-200cs	60	3.0	Nonionic
	Component B : DIMETHICONE	42.0							
	Others	6.25							
KM-910	Component A : DIMETHICONE	36.0	Milky white emulsion	2,500	Dimethicone gum	DM-FLUID-A-200cs	60	5.0	Nonionic
	Component B : DIMETHICONE	24.0							
	Others	6.75							
KM-9729	Component A : DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER	50.0	Milky white emulsion	—	Silicone rubber powder	—	50	5.0	Nonionic
	Others	2.75							
X-52-2042	Component A : DIMETHICONE	33.0	Milky white emulsion	1,000	Dimethicone gum	DM-FLUID-A-200cs	60	3.0	Nonionic
	Component B : DIMETHICONE	27.0							
	Others	6.25							
X-52-2127	Component A : DIMETHICONE	30.0	Milky white emulsion	4,000	Dimethicone gum	DM-FLUID-A-200cs	75	7.0	Cationic
	Component B : DIMETHICONE	45.0							
	Others	4.5							
X-52-2162	Component A : DIMETHICONE	26.0	Milky white emulsion	3,000	Dimethicone gum	DM-FLUID-A-200cs	65	3.5	Nonionic
	Component B : DIMETHICONE	39.0							
	Others	5.25							
X-52-2265	Component A : AMODIMETHICONE	40.0	Milky white emulsion	—	Amino modified silicone	—	40	6.0	Nonionic
	Others	10.1							
X-52-2328	Component A : AMINOPROPYL DIMETHICONE	12.0	Milky white emulsion	2,000	Amino modified gum	DM-FLUID-A-20cs	60	7.0	Nonionic
	Component B : DIMETHICONE	48.0							
	Others	9.5							

(Not specific values)

11 Polyether Modified Silicones

Parameter Grade	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Calculated HLB wt%, EO/5	Cloud Point °C
KF-6011	PEG-11 METHYL ETHER DIMETHICONE	130	1.068	1.450	14.5	65
KF-6011P	PEG-11 METHYL ETHER DIMETHICONE	140	1.062	1.450	14.5	65
KF-6012	PEG/PPG-20/22 BUTYL ETHER DIMETHICONE	1,600	1.030	1.446	7.0	35
KF-6013	PEG-9 DIMETHICONE	400	1.049	1.436	10.0	—
KF-6015	PEG-3 DIMETHICONE	150	1.000	1.420	4.5	—
KF-6016	PEG-9 METHYL ETHER DIMETHICONE	150	1.000	1.417	4.5	—
KF-6017	PEG-10 DIMETHICONE	600	1.007	1.420	4.5	—
KF-6017P	PEG-10 DIMETHICONE	850	1.004	1.420	4.5	—
KF-6004	PEG-32 METHYL ETHER DIMETHICONE	Solid (melting point 45°C)	—	—	9.0	—
KF-6028	PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	900	0.998	1.420	4.0	—
KF-6028P	PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	900	0.997	1.420	4.0	—
KF-6038	LAURYL PEG-9 POLYDIMETHYLSILOXYETHYL DIMETHICONE	700	0.958	1.430	3.0	—
KF-6043	PEG-10 DIMETHICONE	400	1.082	1.454	14.5	71
KF-6048	CETYL PEG/PPG-10/1 DIMETHICONE	2,700	0.963	1.437	3.5	—

* P Grade: odorless versions created using an improved deodorization process.

(Not specific values)

12 Polyglycerin Modified Silicones

Parameter Grade	INCI	Viscosity 25°C, mPa·s	Specific Gravity 25°C	Refractive Index 25°C	Estimated HLB
KF-6100	POLYGLYCERYL-3 DISILOXANE DIMETHICONE	40,000	1.086	1.458	Medium
KF-6104	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE	4,000	0.976	1.409	Low
KF-6105	LAURYL POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE	4,000	0.950	1.426	Low
KF-6106	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE	3,500	0.982	1.412	Low

(Not specific values)

13 Silicone Gels

Parameter Grade	INCI	Component A	Appearance	Penetration (worked), 25°C	Refractive Index 25°C	Base Oil	Cross-linked polymer %
		Component B					
KSG-15	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless transparent paste	420	1.397	KF-995	4-10
	CYCLOPENTASILOXANE						
KSG-1510	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	420	1.389	TMF-1.5	5-10
	METHYL TRIMETHICONE						
USG-103	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless transparent paste	350	1.398	KF-995	8-12
	CYCLOPENTASILOXANE						
KSG-16	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	330	1.400	DM-FLUID-A-6cs	20-30
	DIMETHICONE						
KSG-1610	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	380	1.389	TMF-1.5	15-20
	METHYL TRIMETHICONE						
USG-106	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless transparent paste	420	1.418	ISODODECANE	8-12
	ISODODECANE						
KSG-18A	DIMETHICONE/PHENYL VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	330	1.495	KF-56A	10-20
	DIPHENYLSILOXY PHENYL TRIMETHICONE						
KSG-19	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	360	1.399	DM-FLUID-A-6cs	10-20
	DIMETHICONE						
KSG-016F	DIMETHICONE/VINYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	350	1.398	DM-FLUID-A-6cs	20-30
	DIMETHICONE						
KSG-41A	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	400	1.455	MINERAL OIL	20-30
	MINERAL OIL						
KSG-42A	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	400	1.421	ISODODECANE	15-25
	ISODODECANE						
KSG-43	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	400	1.442	TRIETHYLHEXANOIN	25-35
	TRIETHYLHEXANOIN						
KSG-44	VINYL DIMETHICONE/LAURYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	380	1.447	SQUALANE	25-35
	SQUALANE						
KSG-042Z	LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE/ BIS-VINYLDIMETHICONE CROSSPOLYMER		Colorless transparent paste	330	1.418	ISODODECANE	15-25
	ISODODECANE						
KSG-045Z	LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE/ BIS-VINYLDIMETHICONE CROSSPOLYMER		Colorless translucent paste	350	1.401	KF-995	15-25
	CYCLOPENTASILOXANE						
KSG-048Z	LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE/ BIS-VINYLDIMETHICONE CROSSPOLYMER		Colorless transparent paste	370	1.397	DM-FLUID-2cs	15-25
	DIMETHICONE						
KSG-210	DIMETHICONE/PEG-10/15 CROSSPOLYMER		Colorless milky white paste	400	1.403	DM-FLUID-A-6cs	20-30
	DIMETHICONE						
KSG-240	DIMETHICONE/PEG-10/15 CROSSPOLYMER		Colorless milky white paste	400	1.400	KF-995	15-25
	CYCLOPENTASILOXANE						

(Not specific values)

Silicone Gels

Parameter Grade	INCI	Component A	Appearance	Penetration (worked), 25°C	Refractive Index 25°C	Base Oil	Cross-linked polymer %
		Component B					
KSG-310	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	400	1.450	MINERAL OIL	25-35
	MINERAL OIL						
KSG-320	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	400	1.420	ISODODECANE	20-30
	ISODODECANE						
KSG-330	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	395	1.442	TRIETHYLHEXANOIN	15-25
	TRIETHYLHEXANOIN						
KSG-340	PEG-10/LAURYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	430	1.445	SQUALANE	25-35
	PEG-15/LAURYL DIMETHICONE CROSSPOLYMER						
	SQUALANE						
KSG-320Z	PEG-15/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	360	1.420	ISODODECANE	20-30
	ISODODECANE						
KSG-350Z	PEG-15/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	370	1.404	KF-995	20-30
	CYCLOPENTASILOXANE						
KSG-360Z	PEG-15/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	410	1.408	DM-FLUID-A-6cs	30-40
	DIMETHICONE						
KSG-380Z	PEG-15/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless translucent paste	380	1.400	DM-FLUID-2cs	25-35
	DIMETHICONE						
KSG-710	DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		Colorless milky white paste	400	1.400	DM-FLUID-A-6cs	20-30
	DIMETHICONE						
KSG-810	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		Colorless milky white paste	380	1.450	MINERAL OIL	25-35
	MINERAL OIL						
KSG-820	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		Colorless milky white paste	340	1.420	ISODODECANE	20-30
	ISODODECANE						
KSG-830	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		Colorless milky white paste	380	1.442	TRIETHYLHEXANOIN	15-25
	TRIETHYLHEXANOIN						
KSG-840	LAURYL DIMETHICONE/POLYGLYCERIN-3 CROSSPOLYMER		Colorless milky white paste	380	1.445	SQUALANE	25-35
	SQUALANE						
KSG-820Z	POLYGLYCERYL-3/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	360	1.420	ISODODECANE	20-30
	ISODODECANE						
KSG-850Z	POLYGLYCERYL-3/LAURYL POLYDIMETHYLSILOXYETHYL DIMETHICONE CROSSPOLYMER		Colorless milky white paste	360	1.404	KF-995	20-30
	CYCLOPENTASILOXANE						

(Not specific values)

14 Silicone Acrylates

Parameter	INCI	Component A	Viscosity 25°C, mm ² /s	Content %	Solvent
Grade		Component B			
KP-541	ACRYLATES/DIMETHICONE COPOLYMER	ISOPROPYL ALCOHOL	500-10,000 mPa·s	60	ISOPROPYL ALCOHOL
	ISOPROPYL ALCOHOL				
KP-543	ACRYLATES/DIMETHICONE COPOLYMER	BUTYL ACETATE	100-1,000	50	BUTYL ACETATE
	BUTYL ACETATE				
KP-545	ACRYLATES/DIMETHICONE COPOLYMER	CYCLOPENTASILOXANE	100-500	30	KF-995
	CYCLOPENTASILOXANE				
KP-549	ACRYLATES/DIMETHICONE COPOLYMER	METHYL TRIMETHICONE	500-5,000	40	TMF-1.5
	METHYL TRIMETHICONE				
KP-550	ACRYLATES/DIMETHICONE COPOLYMER	ISODODECANE	100-3,000	40	ISODODECANE
	ISODODECANE				
KP-545L	ACRYLATES/DIMETHICONE COPOLYMER	DIMETHICONE	800-8,000	40	DM-FLUID-2cs
	DIMETHICONE				
KP-578	ACRYLATES/ETHYLHEXYL ACRYLATE/ DIMETHICONE METHACRYLATE COPOLYMER		150-200	100	—
KP-561P	ACRYLATES/STEARYL ACRYLATE/ DIMETHICONE METHACRYLATE COPOLYMER		Solid (melting point 25-35°C)	100	—
KP-562P	ACRYLATES/BEHENYL ACRYLATE/ DIMETHICONE METHACRYLATE COPOLYMER		Solid (melting point 45-55°C)	100	—

(Not specific values)

15 Trimethylsiloxysilicates

Parameter Grade	INCI	Component A	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Resin Content %	Solvent	Film Hardness
		Component B						
X-21-5250	TRIMETHYLSILOXYSILICATE		60	1.034	1.404	50	KF-995	Soft
	CYCLOPENTASILOXANE							
X-21-5250L	TRIMETHYLSILOXYSILICATE		10	0.970	1.399	50	DM-FLUID-2cs	Soft
	DIMETHICONE							
X-21-5616	TRIMETHYLSILOXYSILICATE		10	0.916	1.412	60	ISODODECANE	Soft
	ISODODECANE							
X-21-5249	TRIMETHYLSILOXYSILICATE		60	1.036	1.404	50	KF-995	Medium
	CYCLOPENTASILOXANE							
X-21-5249L	TRIMETHYLSILOXYSILICATE		15	0.980	1.400	50	DM-FLUID-2cs	Medium
	DIMETHICONE							
KF-7312J	TRIMETHYLSILOXYSILICATE		120	1.050	1.405	50	KF-995	Hard
	CYCLOPENTASILOXANE							
KF-7312K	TRIMETHYLSILOXYSILICATE		5,000	1.070	1.410	60	DM-FLUID-A-6cs	Hard
	DIMETHICONE							
KF-7312L	TRIMETHYLSILOXYSILICATE		120	1.000	1.401	50	DM-FLUID-2cs	Hard
	DIMETHICONE							
KF-7312T	TRIMETHYLSILOXYSILICATE		50	1.009	1.401	60	TMF-1.5	Hard
	METHYL TRIMETHICONE							
X-21-5595	TRIMETHYLSILOXYSILICATE		30	0.967	1.416	60	ISODODECANE	Hard
	ISODODECANE							
KF-9021	TRIMETHYLSILOXYSILICATE		2,000	1.070	1.406	50	KF-995	Very hard
	CYCLOPENTASILOXANE							
KF-9021L	TRIMETHYLSILOXYSILICATE		180	1.020	1.402	50	DM-FLUID-2cs	Very hard
	DIMETHICONE							

(Not specific values)

16 Silicone Film Formers

Parameter Grade	INCI	Component A	Viscosity 25°C	Content %	Solvent
		Component B			
NBN-30-ID	NORBORNENE/TRIS (TRIMETHYLSILOXY) SilylnORBORNENE COPOLYMER		300 Pa·s	30	ISODODECANE
	ISODODECANE				
TSPL-30-ID	TRIMETHYLSILOXYSILYL CARBAMOYL PULLULAN		600 mm ² /s	30	ISODODECANE
	ISODODECANE				
TSPL-30-D5	TRIMETHYLSILOXYSILYL CARBAMOYL PULLULAN		8,000 mm ² /s	30	KF-995
	CYCLOPENTASILOXANE				

(Not specific values)

17 Silicone Powders

Parameter Grade	INCI	Appearance	Loss on drying 105°C x 3 h, %	True Specific Gravity	Average Particle Size, µm	Hardness Durometer A
KMP-590	POLYMETHYLSILSESQUIOXANE	White spherical powder	1.0	1.32	2	—
KMP-591	POLYMETHYLSILSESQUIOXANE	White spherical powder	1.0	1.32	5	—
KSP-100	VINYL DIMETHICONE/ METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	1.00	5	30
KSP-101	VINYL DIMETHICONE/ METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	0.98	12	30
KSP-102	VINYL DIMETHICONE/ METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	0.98	30	30
KSP-105	VINYL DIMETHICONE/ METHICONE SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	0.99	2	75
KSP-300	DIPHENYL DIMETHICONE/VINYL DIPHENYL DIMETHICONE/SILSESQUIOXANE CROSSPOLYMER	White spherical powder	0.1	1.11	5	40
KSP-411	POLYSILICONE-1 CROSSPOLYMER	White spherical powder	0.1	0.99	12	22
KSP-441	POLYSILICONE-22	White spherical powder	0.1	0.92	12	—

(Not specific values)

18 Powder Treatments

Parameter Grade	INCI	Viscosity 25°C, mm ² /s	Specific Gravity 25°C	Refractive Index 25°C	Volatile Content 105°C x 3 h, %
F-9W-9P	METHICONE	20	0.999	1.396	< 5
KF-9901	HYDROGEN DIMETHICONE	20	0.971	1.398	< 5
KF-9908	TRIETHOXYSILYLETHYL POLYDIMETHYLSILOXYETHYL DIMETHICONE	60	0.962	1.412	< 5
KF-9909	TRIETHOXYSILYLETHYL POLYDIMETHYLSILOXYETHYL HEXYL DIMETHICONE	45	0.962	1.415	< 5
KP-574	ACRYLATES/TRIDECYL ACRYLATE/TRIETHOXYSILYLPROPYL METHACRYLATE/DIMETHICONE METHACRYLATE COPOLYMER	300	0.981	1.416	< 5
AES-3083	TRIETHOXYCAPRYLYLSILANE	2	0.875	1.417	Boiling point 100°C/2 mmHg

(Not specific values)

19 Powder Dispersions

Parameter Grade	INCI	Powder	Solvent	Powder Content wt%	Appearance	Viscosity 25°C, mPa·s	Specific Gravity 25°C
SPD-T5	CYCLOPENTASILOXANE	TiO ₂	KF-995	40	White-light gray fluid	< 4,000	1.3
	TITANIUM DIOXIDE						
	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE						
	ALUMINUM HYDROXIDE						
	STEARIC ACID						
SPD-T5L	DIMETHICONE	TiO ₂	DM-FLUID-2cs	40	White-light gray fluid	< 4,000	1.2
	TITANIUM DIOXIDE						
	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE						
	ALUMINUM HYDROXIDE						
	STEARIC ACID						
SPD-Z5	ZINC OXIDE	ZnO	KF-995	60	White-light yellow fluid	< 4,000	1.7
	CYCLOPENTASILOXANE						
	POLYGLYCERYL-3 POLYDIMETHYLSILOXYETHYL DIMETHICONE						
	TRIETHOXSILYLETHYL POLYDIMETHYLSILOXYETHYL HEXYL DIMETHICONE						

(Not specific values)


Dimethyl silicone fluid soluble in various solvents

DM-FLUID (dimethyl silicone fluid) : Solubility of medium viscosity grades
 Note that low viscosity grades of DM-FLUID (5 mm²/s and below) also dissolve in ethanol and other solvents, so check prior to use.


Solvent	Result
Solvent naphtha	Soluble
Industrial Gasoline	Soluble
Mineral Spirits	Soluble
Kerosene	Soluble
Cyclohexane	Soluble
n-Hexane	Soluble
n-Heptane	Soluble
Ethyl Ether	Soluble
Diisopropyl Ether	Soluble
Hexyl Ether	Soluble
Ethyl Acetate	Soluble
Butyl Acetate	Soluble
Isopropyl Ether	Soluble
Isopropyl Laurate	Soluble
Isopropyl Palmitate	Soluble
Isopropyl Myristate	Soluble
Methyl Ethyl Ketone	Soluble
Methyl Isobutyl Ketone	Soluble
Lauryl Alcohol	Soluble
Acetone	Partially Soluble
Dioxane	Partially Soluble
Butanol	Partially Soluble
2-Ethylhexanol	Partially Soluble
Amyl Acetate	Partially Soluble
Glacial Acetate Acid	Partially Soluble
Naphthene-based Lubricating Oils	Partially Soluble
Methanol	Insoluble
Ethanol	Insoluble
Cyclohexanol	Insoluble
Ethylene Glycol	Insoluble
Carbitol	Insoluble
Glycerin	Insoluble
Diethylene Glycol Stearate	Insoluble
Propylene Glycol	Insoluble
Liquid Paraffin	Insoluble
Paraffin Wax	Insoluble
Petrolatums	Insoluble
Lubricating Oils	Insoluble
Fatty Acid (other than Glacial Acetic Acid)	Insoluble
Animal and Vegetable Oils	Insoluble
Methyl Phthalate	Insoluble
Water	Insoluble

Volatile Data

■ Volatility at 25°C (measured by filter paper method)




■ Volatility at 37°C (measured by filter paper method)



Bake-on Temperature and Processing Time Methyl Hydrogen Polysiloxane

(without solvent)



* Testing Condition
 Processing Liquid: 10% F-9W-9P Solution
 Testing Substrate: Glass

Solubility Dimethicone

DM-FLUID-L-DM-FLUID

Cosmetic Ingredient	Silicone Fluid : Cosmetic Ingredient					
	10:1		1:1		1:10	
	DM-FLUID-L*	DM-FLUID	DM-FLUID-L*	DM-FLUID	DM-FLUID-L*	DM-FLUID
Cetyl Alcohol	S	I	S	I	S	I
Bees Wax	I	I	I	I	S	I
Lanolin	I	I	I	I	I	I
Glycerine	I	I	I	I	I	I
Liquid Paraffin	S	I	S	I	S	I
Stearic Acid	P	I	I	I	I	I
Squalane	S	S	S	I	S	I
Jojoba Oil	S	I	P	I	P	I
Vaseline	I	I	I	I	S	I

S: Soluble P: Soluble at 60 to 80°C I: Insoluble
* DM-FLUID-L: DM-FLUID-1 to 5cs

Compatibility (20%) Polyether Modified Silicone Fluid, Polyglycerin Modified Silicone Fluid

	KF-6011 6011P	KF-6012	KF-6013	KF-6015	KF-6016	KF-6017 6017P	KF-6028 6028P	KF-6038	KF-6043	KF-6048	KF-6100	KF-6104	KF-6105	KF-6106	KP-578
DM-FLUID-A-6cs (Dimethicone)	I	I	I	I	S	S	S	S	I	I	I	S	S	S	S
TMF-1.5 (Methyl Trimethicone)	I	I	I	S	S	S	S	S	I	S	I	S	S	S	S
KF-995 (Cyclopentasiloxane)	I	I	I	S	S	S	S	S	I	S	I	S	S	S	S
KF-56A (Diphenylsiloxy Phenyl Trimethicone)	S	S	I	S	S	S	S	S	I	S	I	S	S	S	S
Mineral Oil	I	I	I	I	I	I	I	S	I	S	I	I	S	I	I
Isotridecyl Isononanoate	I	S	S	S	S	I	I	S	I	S	I	S	S	S	S
Triethylhexanoin	S	S	S	S	S	S	S	S	S	S	I	I	S	I	S
Ethyl Alcohol	S	S	S	S	S	S	S	I	S	I	S	I	I	I	I
1, 3-Butylene Glycol	S	I	S	I	I	I	I	I	S	I	S	I	I	I	I
Glycerin	I	I	I	I	I	I	I	I	I	I	S	I	I	I	I
Water	S	S	I	I	I	I	I	I	S	I	I	I	I	I	I

S: Soluble I: Insoluble

Handling Precautions

Quality, Storage and Handling

- Since changes in quality may occur due to exposure to heat, humidity, light or acidic or alkaline environments, be sure to close tightly and store in a cool, dark location.
- Wear rubber gloves, safety glasses and other protective gear to prevent contact with the skin and mucous membranes. In case of eye contact, immediately flush eyes with plenty of running water, and consult a physician if necessary.
- To clean, wipe off excess with a rag and then wash with water.
- Please read the Safety Data Sheet (SDS) before use. SDS can be obtained from our Sales Department.

Silicone Division Sales and Marketing Department I

6-1, Ohtemachi 2-chome, Chiyoda-ku, Tokyo, Japan

Phone : +81-(0)3-3246-5132 Fax : +81-(0)3-3246-5361

Shin-Etsu Silicones of America, Inc.

1150 Damar Drive, Akron, OH 44305, U.S.A.

Phone : +1-330-630-9860 Fax : +1-330-630-9855





Shin-Etsu do Brasil Representação de Produtos Químicos Ltda.

Rua Coronel Oscar Porto, 736 11º Andar - 114/115

Paraíso São Paulo - SP Brasil CEP: 04003-003

Phone : +55-11-3939-0690 Fax : +55-11-3052-3904

- The data and information presented in this catalog may not be relied upon to represent standard values. Shin-Etsu reserves the right to change such data and information, in whole or in part, in this catalog, including product performance standards and specifications without notice.
- Users are solely responsible for making preliminary tests to determine the suitability of products for their intended use. Statements concerning possible or suggested uses made herein may not be relied upon, or be construed, as a guaranty of no patent infringement.
- The silicone products described herein have been designed, manufactured and developed solely for general industrial use only; such silicone products are not designed for, intended for use as, or suitable for, medical, surgical or other particular purposes. Users have the sole responsibility and obligation to determine the suitability of the silicone products described herein for any application, to make preliminary tests, and to confirm the safety of such products for their use.
- Users must never use the silicone products described herein for the purpose of implantation into the human body and/or injection into humans.
- Users are solely responsible for exporting or importing the silicone products described herein, and complying with all applicable laws, regulations, and rules relating to the use of such products. Shin-Etsu recommends checking each pertinent country's laws, regulations, and rules in advance, when exporting or importing, and before using the products.
- Please contact Shin-Etsu before reproducing any part of this catalog. Copyright belongs to Shin-Etsu Chemical Co., Ltd.

The Development and Manufacture of Shin-Etsu Silicones are based on the following registered international quality and environmental management standards.

Gunma Complex	ISO 9001 (JCQA-0004)	ISO 14001 (JCQA-E-0002)
Naoetsu Plant	ISO 9001 (JCQA-0018)	ISO 14001 (JCQA-E-0064)
Takefu Plant	ISO 9001 (JQA-0479)	ISO 14001 (JQA-EM0298)

"Shin-Etsu Silicone" is a registered trademark of Shin-Etsu Chemical Co., Ltd. <http://www.shinetsusilicone-global.com/>